

# **SAFETY DATA SHEET**

Creation Date 22-Sep-2009 Revision Date 18-Jan-2018 Revision Number 4

1. Identification

Product Name n-Butyl acetate

Cat No.: BP1135500; B3954; B3961; B3961LC; B3964; B3964LC; B396FB115;

B396FB19; B396FB200; B396FB50; B396RB200; B396RB50; B396RS200; B396RS50; B396SS115; B396SS200; B396SS28;

B396SS50

CAS-No 123-86-4

Synonyms Butyl acetate; Acetic acid, butyl ester; 1-Butyl acetate

Recommended Use Laboratory chemicals.

Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

**Emergency Telephone Number** 

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

## 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Specific target organ toxicity (single exposure)

Target Organs - Central nervous system (CNS).

Category 3
Category 3

Label Elements

Signal Word

Warning

**Hazard Statements** 

Flammable liquid and vapor May cause drowsiness or dizziness



### **Precautionary Statements**

#### Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skir

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### **Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

#### **Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
n-Butyl acetate	123-86-4	100

#### 4. First-aid measures

General Advice If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Inhalation** Move to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and

effects

Breathing difficulties. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting

Revision Date 18-Jan-2018 n-Butyl acetate

Notes to Physician Treat symptomatically

Fire-fighting measures

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed Suitable Extinguishing Media

containers exposed to fire with water spray.

**Unsuitable Extinguishing Media** No information available

27 °C / 80.6 °F **Flash Point** 

Method -No information available

415 °C / 779 °F **Autoignition Temperature** 

**Explosion Limits** 

Upper No data available Lower No data available **Oxidizing Properties** Not oxidising

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

#### Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

Carbon monoxide (CO) Carbon dioxide (CO2)

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	2	0	N/A

### Accidental release measures

**Personal Precautions** 

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** 

Should not be released into the environment. Do not flush into surface water or sanitary

sewer system.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Take precautionary measures against static discharges.

Use spark-proof tools and explosion-proof equipment.

_ /	Н	lar	1d	lin	q	ar	nd	S	tot	rage	9

Handling

Storage

Wear personal protective equipment. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharges.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat

and sources of ignition. Flammables area.

### 8. Exposure controls / personal protection

**Exposure Guidelines** 

Revision Date 18-Jan-2018 n-Butyl acetate

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
n-Butyl acetate	TWA: 50 ppm	(Vacated) TWA: 150 ppm	IDLH: 1700 ppm	TWA: 150 ppm
	STEL: 150 ppm	(Vacated) TWA: 710 mg/m <sup>3</sup>	TWA: 150 ppm	TWA: 710 mg/m <sup>3</sup>
		(Vacated) STEL: 200 ppm	TWA: 710 mg/m <sup>3</sup>	STEL: 200 ppm
		(Vacated) STEL: 950 mg/m <sup>3</sup>	STEL: 200 ppm	STEL: 950 mg/m <sup>3</sup>
		TWA: 150 ppm	STEL: 950 mg/m <sup>3</sup>	_
		TWA: 710 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment.

**Personal Protective Equipment** 

Wear appropriate protective eyeglasses or chemical safety goggles as described by **Eye/face Protection** 

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

When workers are facing concentrations above the exposure limit they must use **Respiratory Protection** 

appropriate certified respirators.

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures** 

### 9. Physical and chemical properties

Liquid

Not applicable

**Physical State** Colorless **Appearance** Odor sweet **Odor Threshold** 7 - 20 ppm 6.2 @ 20°C -90 °C / -130 °F Melting Point/Range **Boiling Point/Range** 126 °C / 258.8 °F 27 °C / 80.6 °F **Flash Point** 1.0 (ether = 1)**Evaporation Rate** 

Flammability (solid,gas) Flammability or explosive limits

Upper No data available No data available Lower **Vapor Pressure** No information available

**Vapor Density** 

**Specific Gravity** 0.881 @ 20C Solubility insoluble

Partition coefficient; n-octanol/water No data available **Autoignition Temperature** 415 °C / 779 °F **Decomposition Temperature** No information available

**Viscosity** 0.83 mPas @ 20°C

Molecular Formula C6H12O2 **Molecular Weight** 116.16 Refractive index 1.393

### 10. Stability and reactivity

**Reactive Hazard** None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Strong bases

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

# 11. Toxicological information

### **Acute Toxicity**

#### **Product Information**

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation
n-Butyl acetate			LC50 = 390 ppm (Rat) 4 h

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
n-Butyl acetate	123-86-4	Not listed				

Mutagenic Effects No information available

Reproductive Effects No information available.

**Developmental Effects**No information available.

**Teratogenicity** No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

delayed

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

## 12. Ecological information

**Ecotoxicity** 

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
n-Butyl acetate	EC50: $= 674.7 \text{ mg/L}, 72h$	Lepomis macrochirus: LC50:	EC50 = 70.0  mg/L  5  min	EC50: = $72.8 \text{ mg/L}$ , $24h$

(Desmodesmus	100 mg/L/96H	EC50 = 82.2 mg/L 15 min	(Daphnia magna)
subspicatus)	Pimephales promelas:	EC50 = 959 mg/L 18 h	
	LC50:17-19 mg/L/96h	EC50 = 98.9 mg/L 30 min	

Persistence and Degradability

Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** 

No information available.

**Mobility** 

Will likely be mobile in the environment due to its volatility.

Component	log Pow
n-Butyl acetate	2.3

### 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

# 14. Transport information

DOT

UN-No UN1123

Proper Shipping Name BUTYL ACETATES

Hazard Class 3
Packing Group III

**TDG** 

UN-No UN1123

Proper Shipping Name BUTYL ACETATES

Hazard Class 3
Packing Group III

IATA

UN-No UN1123

Proper Shipping Name BUTYL ACETATES

Hazard Class 3 Packing Group III

IMDG/IMO

UN-No UN1123

Proper Shipping Name BUTYL ACETATES

Hazard Class 3
Packing Group III

### 15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

#### International Inventories

Component	TSCA	DSL	NDSL	<b>EINECS</b>	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
n-Butyl acetate	Χ	Χ	-	204-658-1	-		Χ	Χ	Χ	Χ	Χ

#### Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants

that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

**CWA (Clean Water Act)** 

•	Component CWA - Hazardous Substances		CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
n	-Butyl acetate	X	5000 lb	-	-

Clean Air Act Not applicable

**OSHA** Occupational Safety and Health Administration

Not applicable

CERCLA Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
n-Butyl acetate	5000 lb	-

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals

#### U.S. State Right-to-Know

Regulations

L	Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Γ	n-Butyl acetate	X	X	X	-	X

### **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

#### Other International Regulations

Mexico - Grade No information available

16. Other information	
-----------------------	--

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 22-Sep-2009

 Revision Date
 18-Jan-2018

 Print Date
 18-Jan-2018

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information

relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**